

PRODUCT DATASHEET SMART WIFI PIN 3,5W 827 230V TW CL G9

SMART+ WIFI PIN G9 TUNABLE WHITE | LED lamps with retrofit pin base G9 with WiFi technology



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury
- Lower energy consumption than incandescent or halogen lamps

Product features

- Controllable via Google Assistant and Amazon Alexa possible
- Network protocol: WiFi
- $\,$ Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- Dimmable
- Lifetime: up to 20,000 h
- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0)





TECHNICAL DATA

Electrical data

Nominal wattage	3.5 W
Construction wattage	3.50 W
Nominal voltage	220240 V
Nominal current	28 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	0.40
Claimed equiv. conventional lamp power	30 W
Operating mode	AC Mains

Photometrical data

Light color (designation) Tunable White Lumen main.fact.at end of nom.life time 0.95 Standard deviation of color matching ≤6 sdcm Nominal luminous flux 320 lm Luminous flux 320 lm Luminous efficacy 91 lm/W Adjustable color temperature 27006500 K Color temperature 27006500 K Color rendering index Ra 80 Flickering metric (Pst LM) 1.0		
Standard deviation of color matching ≤6 sdcm Nominal luminous flux 320 lm Luminous flux 320 lm Luminous efficacy 91 lm/W Adjustable color temperature 27006500 K Color temperature 27006500 K Color rendering index Ra 80 Flickering metric (Pst LM) 1.0	Light color (designation)	Tunable White
Nominal luminous flux 320 lm Luminous efficacy 91 lm/W Adjustable color temperature 27006500 K Color temperature 27006500 K Color rendering index Ra 80 Flickering metric (Pst LM) 1.0	Lumen main.fact.at end of nom.life time	0.95
Luminous flux 320 lm Luminous efficacy 91 lm/W Adjustable color temperature 27006500 K Color temperature 27006500 K Color rendering index Ra 80 Flickering metric (Pst LM) 1.0	Standard deviation of color matching	≤6 sdcm
Luminous efficacy Adjustable color temperature 27006500 K Color temperature 27006500 K Color rendering index Ra 80 Flickering metric (Pst LM) 1.0	Nominal luminous flux	320 lm
Adjustable color temperature 27006500 K Color temperature 27006500 K Color rendering index Ra 80 Flickering metric (Pst LM) 1.0	Luminous flux	320 lm
Color temperature 27006500 K Color rendering index Ra 80 Flickering metric (Pst LM) 1.0	Luminous efficacy	91 lm/W
Color rendering index Ra 80 Flickering metric (Pst LM) 1.0	Adjustable color temperature	27006500 K
Flickering metric (Pst LM) 1.0	Color temperature	27006500 K
	Color rendering index Ra	80
Other constitution (O.A.)	Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM) 0.4	Stroboscope effect metric (SVM)	0.4



Everlight 67-23ST KKE 2700K

Light technical data

Beam angle 300 °	
------------------	--

Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s

Dimensions & Weight



Product weight	10.00 g
Diameter	18.00 mm
Maximum diameter	18 mm
Length	60.00 mm
Width	18.00 mm
Height	18.00 mm
Outer bulb [PICOS]	T18

Lifespan

Number of switching cycles	100000
Lifespan	20000 h
Lumen maintenance at end of service lifetime	0.95

Colors & materials

Product color	Clear
Housing color	Transparent
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
7 tribionit terriporateiro rango	

Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	G9

Capabilities

Dimmable	Yes 1)
Compatible smart home technology	Amazon Alexa / Google Home / Apple Home / Samsung SmartThings

¹⁾ Via App

Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	4.00 kWh/1000h
Standards	CE / EAC / UKCA
Type of protection	IP20

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G9
Connected light source (CLS)	Yes
Color-tuneable light source	Yes
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	2 0.5 W
Networked standby power for CLS	<0.5
Claim of equivalent power	Yes
Chromaticity coordinate x	0.463
Chromaticity coordinate y	0.420
Beam angle correspondence	SPHERE_360
Survival factor	0.90
LED light source replaces a fluorescent light source	No
EPREL ID	1452501
Model number	AC47300,AC47300

EQUIPMENT / ACCESSORIES

- For control via SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Addon technical information	Wifi remote control compatibility list	
PDF	Addon technical information	Wifi remote control compatibility list (DE)	
PDF	Extended installation guide	SMARTWIFIPIN 3,5W/827 230VTWCLG9	
PDF	Declarations of conformity	SMART WIFI PIN 3,5W/827 230V TW CL G9	
PDF	Declarations of conformity UKCA	SMART WIFI PIN 3,5W/827 230V TW CL G9	
PDF	EU Data Act	SMART WiFi Lamps and Luminaires	
	Photometric and lighting design files	Document name	
	Spectral power distribution	Everlight 67-23ST KKE 2700K	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854480430	Folding box 1	56 mm x 78 mm x 82 mm	32.00 g	0.36 dm ³
4099854480447	Shipping box 4	162 mm x 122 mm x 96 mm	201.00 g	1.90 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

G9

- Further information and frequently asked questions (FAQs) at www.ledvance.com/en-int/home-lighting/services/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.