

PRODUCT DATASHEET

FL H M POWER SUPPLY V 300W

FLOODLIGHT HIGH MAST POWER SUPPLY | Floodlight High Mast power supplies



Areas of application

- Outdoor use (IP66)
- Suitable for high mast applications
- Lighting of large areas
- Construction areas
- Industry

Product benefits

- Highly robust and durable
- Optimized product logistic, luminaire heads and power supplies to be ordered separately in stand-alone packaging
- 5 years guarantee

Product features

- Power supply for floodlight high mast luminaire heads
- Joint or separate installation with floodlight high mast power supply
- M16 cable gland for mains cable

TECHNICAL DATA

Electrical data

Nominal wattage	300.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	> 0.90
Total harmonic distortion	< 15 %
Protection class	I

Dimensions & Weight

Length	317.00 mm
Width	201.00 mm
Height	61.00 mm
Product weight	1700.00 g



FL H M POWER SUPPLY V

Materials & Colors

Body material	Aluminum
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40...+50 °C
Temperature range at storage	-40...+70 °C

Type of protection	IP66/IP66
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting location	Wall / Pole / Floor
With light source	No
Replaceable light source	No

Lifespan

Number of switching cycles	100000
----------------------------	--------

Certificates & Standards

Standards	CE / LVD / EMC / ROHS / REACH / SLR / ENEC
Luminaire with limited surface temperature, "D sign"	No

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	Floodlight High Mast
	User instruction / safety instructions	FL H M LUM V_POWER SUPPLY_PONTER HOLDER_ CUT OFF HOOD_ WIRE GUARD
	Legal information	FL H M
	Legal information	FL H M LUM V_POWER SUPPLY_PONTER HOLDER_ CUT OFF HOOD_ WIRE GUARD
	Declarations of conformity	CE Declaration FL H M
	Declarations of conformity UKCA	FL HIGH MAST
	Certificates	FL H M
	Certificates	FL H M LUM V

Tender texts		Document name
	Tender documents	FLOODLIGHT HIGH MAST POWER SUPPLY 300W-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854196508	Folding box 1	230 mm x 70 mm x 328 mm	1843.00 g	5.28 dm ³
4099854196515	Shipping box 4	348 mm x 306 mm x 260 mm	7873.00 g	27.69 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.