

PRODUCT DATASHEET

LISOEV 1465x31 25 17W 940 S130

LINEAR INDIVIDUAL LIGHT SOURCES INDIRECT | Upgrade or replacement light source unit for indirect, diffuse light distribution



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- Easy installation, no tools required for connection
- Homogenous light distribution and reduced glare ($UGR \leq 19$) thanks to IndiviLED® optics
- High performance with CRI90

Product features

- Indirect, diffuse light distribution
- Lifetime (L80/B10): 70,000 h (at 25 °C)
- Beam angle: 90°


TECHNICAL DATA

Electrical data


Nominal wattage	17.00 W
Nominal voltage	45 V
Nominal current	350.000 mA

Photometrical data

Luminous flux	2500 lm
Luminous efficacy	147 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥90
Standard deviation of color matching	3 sdc _{cm}
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	130 °
UGR	19



LISOEV 1465X31 25 17W 940 S130 LEDV 350mA



LISOEV 1465X31 25 17W 940 S130 LEDV 350mA

Dimensions & Weight

Length	1465.00 mm
--------	------------

Width	31.00 mm
Height	11.00 mm
Product weight	337.00 g
Cable length	100.000



1 5m INDIRECT LED MODULE

Materials & Colors

Product color	Grey
Housing color	Grey

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Push-in clamp
Type of protection	IP20
Dimmable	No

Lifespan

Lifespan L70/B50 at 25 °C	100000 h
Lifespan L80/B10 at 25 °C	70000 h
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	25000

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC
-----------	---------------------------------------

Additional product data

Product remark	Available from September 2025
----------------	-------------------------------

Safety advice

– All electrical connections must be made by a qualified person.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	User instruction G11244437
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Safety Insert G11218810
	Legal information	Legal Insert G11244392
	Legal information	LSI insert G11244301
	Declarations of conformity	LN INV
	Declarations of conformity UKCA	LN INV
Photometric and lighting design files		Document name
	IES file (IES)	LISOEV 1465X31 25 17W 940 S130 LEDV 350mA
	LDT file (Eulumdat)	LISOEV 1465X31 25 17W 940 S130 LEDV 350mA
	Light distribution curve type cone	LISOEV 1465X31 25 17W 940 S130 LEDV 350mA
	Light distribution curve type polar	LISOEV 1465X31 25 17W 940 S130 LEDV 350mA
CAD/BIM files		Document name
	CAD STEP 3D	LN INDV INDIRECT G2 LISOEV 1500

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854285028	Folding box 1	36 mm x 1,472 mm x 17 mm	417.00 g	0.90 dm ³
4099854285035	Shipping box 10	1,484 mm x 184 mm x 67 mm	4270.00 g	18.29 dm ³
4099854285042	Shipping box 20	1,504 mm x 204 mm x 158 mm	9450.00 g	48.48 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DIRECT		INHERIT		
EAN	LODEV	EAN	LODEV	EAN LINEAR InheritEDEV
				4089954667000 0 1000 P AMV SW PS BK
				4089954672320 0 1000 P AMV SW PS BK
4089954652000	LODEV 107420 45 408 100 SW 519 BK	408954546170 LODEV 100001 10 100 100 SW 510		40895467000 0 1000 P AMV SW PS BK
				40895467060 0 1000 P AMV SW CA BK BK
				40895467270 0 1000 P AMV SW CA BK BK
				40895467770 0 1000 P AMV SW CA BK BK
				40895467870 0 1000 P AMV SW CA BK BK
				40895467970 0 1000 P AMV SW CA BK BK
4089954652000	LODEV 107420 45 408 100 SW 519 BK	408954546170 LODEV 100001 10 100 100 SW 510		40895468270 0 1000 P AMV SW CA BK BK
				40895468370 0 1000 P AMV SW CA BK BK
				40895468470 0 1000 P AMV SW CA BK BK
				40895468570 0 1000 P AMV SW CA BK BK
				40895468670 0 1000 P AMV SW CA BK BK
				40895468770 0 1000 P AMV SW CA BK BK
4089954652110	LODEV 100001 10 100 100 SW 510 BK	408954546170 LODEV 100001 10 100 100 SW 510		40895468870 0 1000 P AMV SW CA BK BK
				40895468970 0 1000 P AMV SW CA BK BK
				40895469070 0 1000 P AMV SW CA BK BK
				40895469170 0 1000 P AMV SW CA BK BK
				40895469270 0 1000 P AMV SW CA BK BK
				40895469370 0 1000 P AMV SW CA BK BK
				40895469470 0 1000 P AMV SW CA BK BK
				40895469570 0 1000 P AMV SW CA BK BK
				40895469670 0 1000 P AMV SW CA BK BK
4089954652100	LODEV 100001 10 100 100 SW 510 BK	408954546170 LODEV 100001 10 100 100 SW 510		40895469770 0 1000 P AMV SW CA BK BK
				40895469870 0 1000 P AMV SW CA BK BK
				40895469970 0 1000 P AMV SW CA BK BK
				40895470070 0 1000 P AMV SW CA BK BK
				40895470170 0 1000 P AMV SW CA BK BK
				40895470270 0 1000 P AMV SW CA BK BK
				40895470370 0 1000 P AMV SW CA BK BK
				40895470470 0 1000 P AMV SW CA BK BK
				40895470570 0 1000 P AMV SW CA BK BK
				40895470670 0 1000 P AMV SW CA BK BK
				40895470770 0 1000 P AMV SW CA BK BK
				40895470870 0 1000 P AMV SW CA BK BK
				40895470970 0 1000 P AMV SW CA BK BK
				40895471070 0 1000 P AMV SW CA BK BK
				40895471170 0 1000 P AMV SW CA BK BK
				40895471270 0 1000 P AMV SW CA BK BK
				40895471370 0 1000 P AMV SW CA BK BK
				40895471470 0 1000 P AMV SW CA BK BK
				40895471570 0 1000 P AMV SW CA BK BK
				40895471670 0 1000 P AMV SW CA BK BK
				40895471770 0 1000 P AMV SW CA BK BK
				40895471870 0 1000 P AMV SW CA BK BK
				40895471970 0 1000 P AMV SW CA BK BK
				40895472070 0 1000 P AMV SW CA BK BK
				40895472170 0 1000 P AMV SW CA BK BK
				40895472270 0 1000 P AMV SW CA BK BK
				40895472370 0 1000 P AMV SW CA BK BK
				40895472470 0 1000 P AMV SW CA BK BK
				40895472570 0 1000 P AMV SW CA BK BK
				40895472670 0 1000 P AMV SW CA BK BK
				40895472770 0 1000 P AMV SW CA BK BK
				40895472870 0 1000 P AMV SW CA BK BK
				40895472970 0 1000 P AMV SW CA BK BK
				40895473070 0 1000 P AMV SW CA BK BK
				40895473170 0 1000 P AMV SW CA BK BK
				40895473270 0 1000 P AMV SW CA BK BK
				40895473370 0 1000 P AMV SW CA BK BK
				40895473470 0 1000 P AMV SW CA BK BK
				40895473570 0 1000 P AMV SW CA BK BK
				40895473670 0 1000 P AMV SW CA BK BK

– For Guarantee see www.ledvance.com/guarantee

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.