

PRODUCT DATASHEET SENSOR WALL 110DEG IP44 WT

Sensor Wall 110DEG | Stand-alone motion and light sensors for wall mounting with 110° detection range



Areas of application

- Outdoor
- Corridors, entrance areas
- Garages
- Basement
- Arcade passage

Product benefits

- Sensor for optimized energy savings

Product features

- Switch-on by movement
- Type of protection: IP44
- Protection class: II




TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz

Dimensions & Weight



Product weight	89.00 g
Length	60.00 mm
Width	77.00 mm
Height	72.00 mm

Colors & materials

Product color	White
Body material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-10+40 °C
---------------------------	-----------

Capabilities

Dimmable	No
Type of connection	Screw terminal, 3-Pole

Certificates & Standards

Standards	CE / UKCA / EAC
Protection class	II
Type of protection	IP44

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	SENSOR WALL 110DEG IP44	
PDF	Legal information	Safety insert G11219301	
PDF	Declarations of conformity	SENSOR CEILING WALL	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854454134	Folding box 1	67 mm x 80 mm x 94 mm	112.00 g	0.50 dm ³
4099854454141	Shipping box 8	170 mm x 144 mm x 204 mm	1240.00 g	4.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.